



 B202HIII

[illegible]

Paper width	20-54 mm
Paper weight	80-180 g/m²
Interfaces	RS232;USB;Virtual COM

□□□	□□□
□□	8 □ /□□
□□	203 dpi
□□□□□□ /□□	170 □□ /□
□□	PC437, PC850, PC860, PC863, PC865,□□
□□□	□□ , □□□□□ 1□ □ 2□ , □□
□□□	□□ , 90°, 180°, 270°
□□□	□ 20□□ □ 54□□
□□□	□ 80 □ 180 □ /□ ²

RAM	RAM 200 MB
OS	CUSTOM/POS, SVELTA
Porte	RS232 + USB COM
Memoria	64 KB
Memoria	18 MB
Memoria	Memoria 2 MB
SD/MMC	SD = 2 GB
Software	Windows® 32/64 bit — WHQL CUPS Linux 32/64 bit COM Linux Windows 32/64 bit ™ iOS
Software	PrinterSet, CustomPowerTool
Alimentazione	24 Vdc ± 10% 100 Vac 240 Vac
Alimentazione	1.2A (12,5%)
Alimentazione	150 W / 100M W
Alimentazione	100 W W
Alimentazione	0°C + 50°C
Dimensioni	194 mm x 155 mm x 133 mm 364 mm (L) x 133.2 mm (H) x 155 mm (W) 363.5 mm (L) x 155 mm (H) x 133.2 mm (W)
Alimentazione	2,8 W 3,8 W 3 W

MODELLI DISPONIBILI

CODICE	DESCRIZIONE
911AP030100333	PRINTER B202HIII USB RS232