

KM216HIII

KM216HIII is a cutting-edge A4 format printer. An advanced device, part of Custom's offering for the Aviation sector, capable of printing both boarding passes and travel information documents thanks to its high print quality and large format. Its simple and robust motorized ejector, long-lasting print head, and autocutter make it reliable and the ideal choice for the Aviation market.



CARATTERISTICHE PRINCIPALI

Adjustable paper feed, Simple and robust motorized ejector, Prevention of Dot Damage, Highly reliable cutter, Full remote management via internal web server, Automatic email sending for service purposes, Remote update of logo and fonts, and Drivers available on the printer's flash disk.

SPECIFICHE TECNICHE

Usage

GPP Wide format

SCHEDA TECNICA

Printing method	Thermal with fixed head
Resolution	200 dpi (8 dots/mm)
Printing speed (max.)	125 mm/sec
Paper width	194-216 mm
Paper weight	58-78 g/m ²
External roll diameter	180 mm
Roll core diameter	25 mm
Sensors	Paper presence; print head temperature; paper presence at output; black mark; cover open; optional near paper end; automatic cutter error
Emulation	CUSTOM/POS
Interfaces	RS232; USB; Ethernet

Print driver	Windows® (32/64 bit); CUPS Linux (32/64 bit); Virtual COM; Android™ ; iOS
Software tools	PrinterSet; CustomPowerTool; Status Monitor; Custom Windows® API; Driver Manager
Special features	A4 or US Letter format; damaged dot prevention
Power supply	24 Vdc ± 10%
Typical consumption	3.1 A
Print head life	100 km / 100M pulses
Cutter	Full cut
Cutter life	300,000 cuts
Operating temperature	0°C ~ 50°C
Dimensions (L x W x H)	170 x 274 x 84 mm
Weight	3.76 kg
Package contents	Device; quick guide; NPE sensor; NPE cable; fixing brackets with screws; power cable harness

GALLERIA



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
915AS060100700	PRINTER KM216HIII ETH USB RS232 EJECTOR