

KPM302III

- High printing quality at 200 dpi (**300 dpi optional**)
- Ticket width: from 20 to 82.5 mm
- Printing > 200 mm/sec
- Heavy-duty applications
- 1D and 2D barcode printing: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, AZTEC, QR CODE
- True Font character support, any language available.
- Ethernet, RS232 and USB (or Virtual COM) interfaces
- Highly reliable cutter: over 1,500,000 cuts
- Sensors: 4-position black mark sensor and gap /hole mark sensor (settable via software); ticket presence sensor



CARATTERISTICHE PRINCIPALI

RFID Version: multiple SAM management, Enhanced print head for sharp and precise printing, Powerful 32-bit processor, internal barcode scanner ideal for card validation and fraud prevention – optional, and automatic email sending for service purposes.

Other listed elements include **Remote update of logo and fonts (True Font)**, **Drivers available on the printer's flash disk**, Sw EasyMyfare for reading/writing data on Mifare tags, and Sw EthLocator to find connected network printers and configure their parameters.

SPECIFICHE TECNICHE

Paper width	20-82.5 mm
Paper weight	80-255 g/m²
External roll diameter	300 mm

SCHEDA TECNICA

Printing method	Thermal with fixed head
Resolution	200 dpi (8 dots/mm)
Printing speed (max)	200 mm/sec
Paper width	20-82.5 mm, adjustable in 2 mm increments
Paper weight	80-255 g/m²
External roll diameter	300 mm
Roll core diameter	25 mm
Sensors	Paper presence; printhead temperature; paper presence on output; adjustable detectors for black mark or translucent gap/hole; cover open; optional low paper sensor; autocutter error
Emulation	CUSTOM/POS; SVELTA
Interfaces	RS232; USB; Ethernet
Print Driver	Windows® (32/64 bit); CUPS Linux; Virtual COM; OPOS; Android™; iOS
Software Tools	PrinterSet; Custom Power Tool; Status Monitor; Custom Windows® API; Driver Manager
Special features	Wristband; full cut; ultra-heavy-duty design; RFID HF; RFID UHF; triple feeder
Power supply	24 Vdc ± 10%
Typical consumption	0.8 A
Print Head Life	100 km / 100M pulses
Cutter	Full cut
Cutter life	1,500,000 cuts
Operating temperature	0°C ~ 50°C
Dimensions (L x W x H)	191 x 160 x 123 mm
Weight	3.5 kg
Box contents	device; quick guide; power cable harness; paper width reducer; fixing brackets (x2); cut-and-drop kit; burster kit; ruler

GALLERIA



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
915AV210100700	PRINTER KPM302III ETH USB RS232