



CARATTERISTICHE PRINCIPALI

P3X is the ideal **thermal POS printer** for the retail and hospitality sectors. Thanks to its compact and robust design, it adapts to any point-of-sale environment. The device also integrates well into POS systems running **Windows®**, **Android™**, **iOS®** and **Linux**. P3X is available **with triple interfaces**: USB (or Virtual COM) - Ethernet - Serial.

SPECIFICHE TECNICHE

Paper width	57-80 mm
Printing speed (max)	200 mm/sec
Interfaces	Ethernet;USB;Virtual COM;RS232;Cash Drawer
Print Driver	Windows (32/64 bit);CUPS Linux (32/64 bit);Virtual COM;OPOS;JavaPOS;Android;iOS

SCHEDA TECNICA

Printing method	Thermal with fixed head
Resolution	200 dpi (8 dots/mm)
Maximum printing speed	200 mm/sec
Character set	International fonts: 54 character code tables; extended Chinese GB18030-2000; Korean PC949; Chinese BIG5
Supported barcodes	UPC-A; UPC-E; EAN13; EAN8; CODE39; ITF; CODABAR; CODE93; CODE128; CODE32; PDF417; DATAMATRIX; AZTEC; QR CODE
Printing direction	Normal; 90°; 180°; 270°
Paper width	57 mm; 80 mm
Paper weight	55-90 g/m²
Printing width	52.76 mm
External roll diameter	80 mm
Sensors	Print head temperature; paper presence; cover open
Emulation	CUSTOM/POS

Interfaces	RS232; USB; Ethernet; drawer port; optional wireless adapter: Wi-Fi 4 (b/g/n); Bluetooth BLE 4.2
Data buffer	16 kB
Print drivers	Windows® (32/64 bit); Linux CUPS (32/64 bit); Virtual COM for Linux or Windows® (32/64 bit); OPOS; JavaPOS; Android™; iOS
Software tools and SDKs	PrinterSet for Windows® and Linux; Android™ PrinterSet; CustomPowerTool; VCOM Service; Custom Windows® API; Custom Linux API; Custom Android™ API; Custom iOS API
Printer mounting	Horizontal; vertical
Power supply	24 Vdc ± 10%
Typical consumption	1.2 A
Print head life	150 km / 100M pulses
Cutter	Full and partial cut
Cutter life	1,000,000 cuts
Operating temperature	0°C ~ 40°C
Dimensions (L x W x H)	190 x 142 x 135.5 mm
Weight	1.1 kg
Package contents	Device; quick guide; AC adapter; standard AC power cord; paper width guide with screws

GALLERIA



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
911MH020100733	PRINTER P3X 80MM ETH USB RS232