

"sixload"
EAN 8, CODE 39, ITF, CODABAR. S'PRINT-
RS232.



S'PRINT



 "sixload"





Paper width	57 mm
Printing speed (max)	50 mm/sec
Interfaces	RS232;Virtual COM
Print Driver	Windows (32/64 bit)

□□□	□□□
□□	8 dots/□□
□	24 (□□ 40/42 □□)
□□	203dpi
□□□□□ /□□	50□□□□□□□□□□□□□□
□□	ASCII □□ , □□

Modello	Modello / Versione
Stampa	Stampa
Velocità	58 mm
Velocità	60µm
Velocità	57.5 mm ± 1mm
Stampa	CUSTOM
Stampa	Stampa 9 mm, RS232
Stampa	128 Byte
Stampa	32 KB
Stampa	1 mm 384 x 85 mm
Stampa	Windows® 32/64 bit --- WHQL
Stampa	9 - 48 VDC / 11VA
Stampa	1200 - 230 mA
MTBF	260.000 mm (mm)
Stampa	0°C + 50°C
Stampa	CE
Stampa	(LxPxA) 146x88x65mm
Stampa	0.370 mm (mm)

GALLERIA



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
911DE010100133	PRINTER S'PRINT RS232 24 COL BLACK
911DE010500112	PRINTER S'PRINT RS232 40 COL BICOLOR