

S'PRINT S

The S'PRINT thermal printers provide great capacity and performance with reduced size and weight.

Automatic paper loading with patented "sixload" system. Equipped with paper end sensor and black mark sensor. The printer supports an upgradable customer logo and can print the most used barcodes EAN 13, EAN 8, CODE 39, ITF, CODABAR. S'print-s is powered via an external power supply and comes equipped with serial RS232 interface. It is the ideal solution for applications such as instruments, receipt, coupon and report printing, also for banking operations.



CARATTERISTICHE PRINCIPALI

The S'PRINT thermal printers provide great capacity and performance with reduced size and weight.

Automatic paper loading with patented "sixload" system. Equipped with paper end sensor and black mark sensor. The printer supports an upgradable customer logo and can print the most used barcodes EAN 13, EAN 8, CODE 39, ITF, CODABAR. S'print-s is powered via an external power supply and comes equipped with serial RS232 interface. It is the ideal solution for applications such as instruments, receipt, coupon and report printing, also for banking operations.

SPECIFICHE TECNICHE

Paper width	57 mm
Printing speed (max)	50 mm/sec
Interfaces	RS232;Virtual COM
Print Driver	Windows (32/64 bit)

SCHEDA TECNICA

Printing method	Thermal with fixed head
Resolution	200 dpi (8 dots/mm)
Maximum printing speed	50 mm/sec

Character set	Standard ASCII; international
Supported barcodes	INTERLEAVED 2/5; EAN13; EAN8; CODE39; CODABAR
Printing direction	Normal; 90°; 180°
Paper width	57 mm
Paper weight	55-60 g/m²
Printing width	48 mm
External roll diameter	50 mm
Sensors	Near paper end; black mark alignment
Emulation	CUSTOM/POS
Interfaces	RS232
Data buffer	128 bytes
Print drivers	Windows® (32/64 bit)
Power supply	From 9 Vdc to 48 Vdc
Typical consumption	1200-230 mA
Print head life	50 km / 100M pulses
Operating temperature	0°C ~ 50°C
Dimensions (L x W x H)	146 x 88 x 65 mm
Weight	0.34 kg
Package contents	Device; quick guide; AC adapter; adapter plugs; serial cable

GALLERIA



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
911DE010100133	PRINTER S'PRINT RS232 24 COL BLACK
911DE010500112	PRINTER S'PRINT RS232 40 COL BICOLOR