

TG02H

Extremely compact and versatile ticket printer, for easy installation and panel mounting. TG02H is available with black plastic bezel.

- Best quality print quality (200 DPI)
- Paper width: 57mm
- Printing > 80 mm/sec
- Up to 90mm paper roll diameter
- RS232 + USB interfaces (serial TTL with welding)
- Highly reliable tear off system
- Sensors: head temperature, paper presence, near paper end, anti-jamming
- Power supply: 12V and 24V



CARATTERISTICHE PRINCIPALI


1D/2D barcode printing capability (QR CODE), Built-in international fonts: any language available, Patented anti-jam system, External applications: operating temperature -20/+70°C, Low power consumption in standby, Roll holder included, gaming machine application and queue management system application. Details are organised to facilitate quick consultation and comparison with products in the same category.

SPECIFICHE TECNICHE

Paper width	57 mm
Paper weight	55-60 g/m²
External roll diameter	90 mm
Interfaces	RS232;USB;AUX

Printing method	Thermal with fixed head
Resolution	200 dpi (8 dots/mm)
Printing speed (max)	80 mm/sec
Paper width	57 mm
Paper weight	55-60 g/m ²
External roll diameter	90 mm
Roll core diameter	12 mm
Sensors	Head temperature; paper presence; near-paper-end sensor; anti-jam sensor
Emulation	CUSTOM/POS; TG558
Interfaces	TTL; RS232; USB
Print Driver	Windows® (32/64 bit); Linux (32/64 bit); Virtual COM; Android™; iOS
Software Tools	PrinterSet; Custom Power Tool; Status Monitor; Custom Windows® API; Driver Manager
Special features	12 V or 24 V; tear-off; anti-jam system; roll holder included
Power supply	12 Vdc ± 10%; 24 Vdc ± 10%
Typical consumption	0.7 A; 0.4 A
Print Head Life	50 km / 100M pulses
Cutter	Tear-off
Operating temperature	-20°C ~ 70°C
Dimensions (L x W x H)	129 x 100 x 120 mm
Weight	0.33 kg
Box contents	device; quick guide; paper roll retaining discs

GALLERIA



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
915HZ010300300	PRINTER TG02H USB RS232