

TK180 METAL



CARATTERISTICHE PRINCIPALI

TK180 Metal is the smallest combined printer with high reliability features. The printer can handle paper thickness up to 255 gsm and tickets from 20mm to 82.5 mm wide. TK180 Metal is equipped with a powerful internal processor and Hot swap function. Speed > 200 mm/s. RS232 + USB + ETH interfaces. The printer Supports True Font characters and 2D barcodes, and is capable of managing logo drag&drops. In addition to the most common sensors, it is also equipped with the new mobile sensor, capable of identifying black marks or gaps on the non-thermal side.

SPECIFICHE TECNICHE

Paper width	20-82.5 mm
Paper weight	70-255 g/m²
Interfaces	RS232;USB;Ethernet
Roll diameter	200 mm

SCHEDA TECNICA

Printing method	Thermal with fixed head
Resolution	200 dpi (8 dots/mm)
Printing speed (max)	200 mm/sec
Paper width	20-82,5 mm
Paper weight	70-255 g/m²
Paper thickness	Max 270 µm
External roll diameter (max)	200 mm
Roll core diameter	25 mm
Sensors	Paper presence; printhead temperature; paper presence on output; adjustable detectors for black mark or translucent gap/hole; cover open; optional low paper sensor; autocutter error

Emulation	CUSTOM/POS; SVELTA
Interfaces	RS232; USB; Ethernet
Print Driver	Windows® (32/64 bit); Linux (32/64 bit); Virtual COM (Linux or Windows® 32/64 bit); OPOS; Android™; iOS
Software Tools	PrinterSet; CustomPowerTool; Status Monitor
Special features	compact; desktop; full cut; tear-off; wristband; labels; robust; RFID UHF
Power supply	24 Vdc ± 10%
Typical consumption	1,5 A
Print Head Life	100 Km / 100M pulses
Cutter	full cut or tear-off
Cutter life	1.000.000 cuts
Operating temperature	0°C ~ 40°C
Dimensions (L x W x H)	122,6 x 145,6 x 85 mm
Weight	2,2 Kg
Box contents	device; quick guide; power supply; power cord; paper block guide; paper width reducer

GALLERIA



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
911HL010300733	PRCT TK180 ETH USB BLACK AERO E06 CN