

TK202III - TK302III

TK202III - TK302III are the most advanced ATB and BTP ticket printers on the market, designed for applications that involve high workloads and require reliability and high performance. TK202III - TK302III are completed by a two-line display with 20 characters. They are equipped with native AEA/ITPS firmware for perfect integration into the CUTE and CUPPS platforms. TK202III - TK302III have an automatic sensor calibration function that is automatically activated every time paper is loaded and prevents any ticket waste thus contributing to environmental sustainability and reducing management costs.



CARATTERISTICHE PRINCIPALI

Resistant, Highly reliable and robust, Same model for ATB and BTP, Tear bar on 2 sides (TK202III), Robust autocutter (TK302III), RFID (optional), Prevention of damaged Dot elements and automatic ticket length detection.

SPECIFICHE TECNICHE

Options	RFID;Multifeeder
Strenght	Ultra Heavy Duty
Usage	ATB;BTP;GPP

SCHEDA TECNICA

Printing method	Thermal with fixed head
Resolution	200 dpi (8 dots/mm)
Printing speed (max.)	200 mm/sec
Paper width	Compliant with IATA Resolution 740, 722e and RP 1740
Paper thickness	According to IATA specifications
Paper roll diameter	300 mm
Supported barcodes	UPC-A; UPC-E; EAN13; EAN8; CODE39; ITF; CODABAR; CODE93; CODE128; CODE32; PDF417; DATAMATRIX; AZTEC; QR CODE

Sensors	Paper presence; print head temperature; paper presence at output; adjustable black mark or translucent gap/hole detectors; cover open; optional near paper end; automatic cutter error
Emulation	ATB; BTP; GPP
Firmware	Native AEA/ITPS support from 2007 to 2022
Interfaces	RS232; USB; Ethernet
Drivers	Windows® (32/64 bit); CUPS Linux (32/64 bit); Virtual COM (32/64 bit); Android™
Software tools	PrinterSet; CustomPowerTool; Status Monitor; Custom Windows® API; AeroVcomService remote monitor configuration tool
Power supply	24 Vdc ± 10%
Typical consumption	0.8 A
Print head life	100 km / 100M pulses
Cutter	Two-sided tear bar
Operating temperature	0°C ~ 40°C
Dimensions (L x W x H)	252 x 216 x 192.6 mm; 366.2 x 216 x 192.6 mm
Weight	4 kg
Package contents	Device; quick guide; power supply; paper width reducer; ruler

GALLERIA



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
911BB070300713	PRINTER TK302III ETH USB RS232 AVIATION
911BB090300713	PRINTER TK302III RFID UHF ETH USB RS232 AVIATION
911BB080300713	PRINTER TK302III ATB TF888 ETH USB RS232 AVIATION
911BD050300313	PRINTER TK202III USB RS232 AVIATION
911BD070100313	PRINTER TK202III RFID UHF USB RS232 AVIATION