

TK862

TK862 is the only compact airport printer able to combine **metallic case, high speed and refined design together with a lower TCO** (Total Cost of Ownership). This device is **Energy Star** certified and offers efficient and innovative functionalities like the **auto-calibration**, that avoid the waste of paper through auto-calibrating sensors that can adapt to an infinite number of media types. The **multi feeder** version is useful for reducing waiting times by increasing printing volumes, the **RFID** configuration allows you to have a product already prepared for future needs. **Veriprint®** technology allows to instantly validate the barcode of a bag tag or boarding pass preventing a baggage or a passenger are checked-in but carrying an unreadable luggage tag / barcoded boarding pass. TK862 is compatible with **AERO VCOM SERVICE** which supports the most sophisticated AEA communication standards and allows per-airline **dedicated configurations** within standard AEA parameters.




CARATTERISTICHE PRINCIPALI

Entre las características indicadas se encuentran **Ultra resistente, Altamente fiable y robusta, Muy rápida y potente**, Mismo modelo para ATB y BTP y Sensores Contact Imager (CIS) para la detección de espacios vacíos en lugar de los tradicionales sensores de tacha negra, para mejorar la fiabilidad y reducir las operaciones de limpieza y alinearse virtualmente con cualquier marca/foro/logo.

Entre otros elementos reportados se incluyen **Veriprint Barcode Validation (opcional), Cortadora extra resistente**, RFID (opcional), Prevención de puntos dañados, Detección automática de la longitud del billete y Auto-carga de papel completa sin desperdicio.

SPECIFICHE TECNICHE

Options	RFID;Multifeeder
Strenght	Ultra Heavy Duty
Usage	ATB;BTP;GPP



MODELLI DISPONIBILI

CODICE	DESCRIZIONE
911LU010400733	PRINTER TK862 ETH USB RS232 AVIATION
911LU010800733	PRINTER TK862 EJC ETH USB RS232 AVIATION
911LU011400733	PRINTER TK862 EJC DF ETH USB RS232 AVIATION
911LU020300733	PRINTER TK862 VERIPRINT ETH USB RS232 AVIATION