

TL60III

- Metal frame (galvanized/aluminium alloy)
- High print quality (200 DPI)
- Paper width: 60mm
- Paper thickness: from 63 to 85 µm
- Printing > 140 mm/sec
- RS232 and USB interfaces
- Barcodes: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QRCODE
- Characters: European, International, Portuguese, Nordic, Arabic, Chinese and Russian
- Highly reliable cutter: over 1,000,000 cuts
- Sensors: paper presence and head opening



CARATTERISTICHE PRINCIPALI

Very compact: only 77 mm in height, Ideal for harsh environments, from -20°C to +70°C, Multi-position paper support: top, bottom, or rear, Paper roll diameter up to 80mm, and a metal structure that ensures greater rigidity of the printing mechanism and better heat dissipation of the motor, for improved stability and reliability over time.

Other listed elements include **Enhanced roller-print head pressure distribution for better print quality** and **Kiosk self-service application**.

SPECIFICHE TECNICHE

Paper width	60 mm
Paper weight	55-80 g/m²
External roll diameter	80 mm

SCHEDA TECNICA

Printing method	Thermal with fixed head
Resolution	200 dpi (8 dots/mm)
Printing speed (max)	140 mm/sec
Paper width	60 mm
Paper weight	55-80 g/m²
External roll diameter	80 mm
Roll core diameter	12 mm
Sensors	Head temperature; paper presence; printhead open
Emulation	CUSTOM/POS; TGH
Interfaces	RS232; USB
Print Driver	Windows® (32/64 bit); Linux (32/64 bit); Virtual COM; Android™
Software Tools	PrinterSet; Custom Power Tool; Status Monitor; Custom Windows® API; Driver Manager
Special features	Full and partial cut; ejector model; roll holder included; optional near-paper-end sensor
Power supply	24 Vdc ± 10%
Typical consumption	0.65 A
Print Head Life	50 km / 100M pulses
Cutter	TL60III: partial or full cut TL60III EJ: full cut
Cutter life	1,000,000 cuts
Operating temperature	-20°C ~ 70°C
Dimensions (L x W x H)	130 x 105 x 77 mm
Weight	0.8 kg
Box contents	device; quick guide

MODELLI DISPONIBILI

CODICE	DESCRIZIONE
915CJ040100300	PRINTER TL60III USB RS232
915CJ040200300	PRINTER TL60III USB RS232 EJECTOR